

# GL612N/GL622N

## Applications

### General Construction

- Leveling concrete forms and footers
- Vertical alignment such as wall, columns and form alignment

### Machine Guidance Compatible

- Dual slope grading and steep slope excavating
- Slope work for sports fields, tennis courts, driveways, parking garages, ramps

### Pipe and Drainage Installations

- Over-the-Top sewer and drainage pipe installations
- Trenching and drainage



## Easy-To-Use, Full Featured Automatic Grade Lasers



The Spectra Precision® GL612N single grade and GL622N dual grade lasers are automatic self-leveling, rugged and cost-effective. An intuitive keypad and graphic display make all grade and alignment functions easy to use and greatly reduces setup time and increases productivity. A matching remote control also simplifies all level, grade, and vertical alignment setup tasks.



### Key Features

#### Ultimate Control of X/Y Axes

- Fully automatic up to +/-25% grade on X/Y axes
- Automatic Axis Features (X Axis - only GL622N)
  - High Precision Axis Alignment (only GL622N)
  - Simplified Grade Match: measures and displays the existing grade over unknown ground
  - Complete PlaneLok: automatically locks on the laser beam to an existing elevation
- Alignment range for both axes is +/-40°
- Fully automatic vertical leveling
- Fingerprint function - detects only the laser beam of the paired transmitter

#### Built for Today's Jobs

- Withstands a 1 m (3 ft) drop onto concrete
- Long operating range - 800 m (2,600 ft) diameter
- Long operating radio range - 150 m (490 ft)
- Intuitive keypad and graphic display
- Password secured
- Mask mode
- Various power options
- Automatic temperature compensation
- Electronic leveling vibration filter

### User Benefits

- Quickly adapts to site requirements
- Simplifies level, grade and vertical alignment setups
- Reduces time to do steep slope work and drainage installation
- Increases reliability, accuracy and durability
- Economize operating costs



# GL612N/GL622N – Maximum Versatility for Leveling, Grading and Vertical Alignment

## GL612N/GL622N Specifications

- Leveling accuracy<sup>1,3</sup>: ± 0.5 mm/10 m, 1/16" @ 100 ft, 10 arc seconds
- Grade accuracy<sup>1,3</sup>: ± 1.0 mm/10 m, 1/8" @ 100 ft, 20 arc seconds
- Operating diameter<sup>1,2</sup>: appr. 800 m (2600 feet) with detector
- Grade range (Y, X-GL622N): ± 25% both axes (not simultaneously)
- Rotation: 300, 600, 750 rpm
- Laser type: 639 nm
- Laser class : Class 2
- Self-leveling range: appr. ± 14°
- Leveling indicators: LCD indications and LED flashes
- Radio range (HL760)<sup>1,2,4</sup>: up to 150 m (490 ft)
- Power source: NiMH battery pack
- Battery life<sup>1</sup>: 35 hours NiMH
- Operating temp.: -20°C to 50°C (-4°F to 122°F)
- Storage temp.: -20°C to 70°C (-4°F to 158°F)
- Tripod attachments:
  - 5/8 x 11 horizontally and vertically
- Dust and waterproof: Yes - IP67
- Weight: 3.1 kg (6.8 lbs)
- Low voltage indication: LCD battery indicator
- Low voltage disconnection: unit shuts off
- Warranty: 5 Years

## HL760 Digital Readout Receiver

- Highly versatile receiver for basic and advanced leveling and aligning applications
- Works with GL612N/GL622N in automatic Axis Alignment (only GL622N), Grade Match and PlaneLok applications
- Key Features:
  - Digital readout of elevation
  - Exact distance from grade displayed
  - Anti-strobe sensor to prevent false reading from jobsite strobe lights
  - Large reception height to ease beam reception
  - Withstands a drop of up to 3m (10ft)
  - Radio communication - works with another HL760 for long range wireless remote display and monitoring capability
  - "Fingerprint" function of the HL760 DRO receiver only accepts the beam from the laser it is paired with
- User Benefits:
  - No need to go "on-grade" to measure;
  - Saves considerable time
  - Reduces rework by allowing remote monitoring
  - Increases reliability, accuracy and durability

## RC602N Remote Control Specifications

- Operating range<sup>1,2,4</sup>: up to 150 m (490 ft)
- Power source: 2 x 1.5V AA alkaline batteries
- Battery life<sup>1</sup>: 130 hours
- Dust and waterproof: Yes - IP66
- Weight: 0.26 kg (0.57 lbs)

## HL760 Laserometer Specifications

- Digital readout units: mm, cm, ft, in, frac. in
- Reception height: 127 mm (5 inches)
- Six On-grade sensitivities:
  - Ultra Fine 0.5 mm (~1/32 in)
  - Super Fine 1 mm (~1/16 in)
  - Fine 2 mm (~1/8 in)
  - Medium 5 mm (~1/4 in)
  - Coarse 10 mm (~1/2 in)
  - Calibration Mode 0.1 mm (~1/64 in)
- Battery life (2 x AA):
  - 60+ hours continuous operation
- Auto shut-off: 30 minutes/24 hours
- Operating temp.: -20°C to 50°C (-4°F to 122°F)
- Dust and waterproof: Yes - IP67
- Weight: 0.27 kg (9.5 oz)
- Warranty: 3 Years "No Excuses"

<sup>(1)</sup> at 21° Celsius (70° F)

<sup>(2)</sup> under optimal atmospheric circumstances

<sup>(3)</sup> along the axis

<sup>(4)</sup> Height of instruments 1m (e.g. with tripod)



RC602N Radio Remote Control for all applications



HL760 Laserometer to measure and display beam location

## Contact Information:

### NORTH AMERICA

Trimble Spectra Precision Division  
5475 Kellenburger Road • Dayton, Ohio 45424 • USA  
Toll Free +1-888-272-2433 • Fax +1-937-245-5489  
[www.spectralasers.com](http://www.spectralasers.com)

### EUROPE

Trimble Kaiserslautern GmbH  
Am Sportplatz 5 • 67661 Kaiserslautern • Germany  
Phone +49-6301-711414 • Fax +49-6301-32213



To locate your nearest distributor, please visit the Dealer Locator section at [www.spectralasers.com](http://www.spectralasers.com) or [www.trimble.com](http://www.trimble.com). Specifications and descriptions are subject to change without notice. Please visit [www.spectralasers.com](http://www.spectralasers.com) or <http://www.trimble.com/construction-tools/> for the latest product information.

© 2017, Trimble Inc. All rights reserved. Trimble, the Globe & Triangle logo and Spectra Precision are trademarks of Trimble Inc., registered in the United States Patent and Trademark office and in other countries. All other trademarks are the property of their respective owners. PN 022507-288C (06/17)

SCAN THIS  
CODE FOR MORE  
INFORMATION

