



Trimble TCU5

MODEL 2

CONTROLLER FOR TRIMBLE S SERIES TOTAL STATIONS



Take control of the way you work.

KEY FEATURES

- ▶ Combines latest Trimble® Access™ field software with Trimble S Series Total Stations
- ▶ Wi-Fi connectivity, including Trimble Sync Manager support
- ▶ Android™ operating system
- ▶ 5-inch multi-touch screen
- ▶ Portability for ease of data transfer in the office connecting via the docking station
- ▶ In-the-field flexibility to be an integrated on-board control unit or robotic data collector
- ▶ Bluetooth connectivity for GNSS receivers and auxiliary devices

Learn more:
geospatial.trimble.com/TCU5

Trimble TCU5 MODEL 2 - CONTROLLER

STANDARD FEATURES SYSTEM

- Wi-Fi IEEE 802.11 a/b/g/n 2.4 GHz / 5 GHz dual-band
- 5.0 inch LED-backlight screen with capacitive multi-touch
- i.MX 6 series 32-bit MPU, Dual ARM Cortex-A9 core
- 2 GB RAM
- 16 GB flash memory
- Integrated speaker
- Bluetooth® v 4.1

OPERATING SYSTEM

- Android 7.1.1 (Nougat)
- Languages available: Afrikaans, Azerbaijani, Bulgarian, Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hindi, Hungarian, Italian, Japanese, Korean, Lithuanian, Norwegian (Bokmål), Polish, Portuguese (Portugal and Brazil), Romanian, Russian, Serbian (Cyrillic), Simplified Chinese, Spanish, Swedish, Turkish
- Software package includes: Trimble Installation Manager

STANDARD ACCESSORIES

- USB cable
- Docking station including power supply

OPTIONAL ACCESSORIES

- Pole bracket
- Robotic holder

SOFTWARE COMPATIBILITY

- Trimble Access
- Trimble Precision SDK for Android

HARDWARE COMPATIBILITY

- S5, S7, S9, S9 HP Robotic Total Stations

TECHNICAL SPECIFICATIONS PHYSICAL

Size	176 mm x 112 mm x 30 mm (6.9 in x 4.4 in x 1.2 in)
Weight	.437 g (0.96 lb)
Processor	i.MX 6 series 32-bit MPU, Dual ARM Cortex-A9 core
Clock frequency	.800 MHz
Memory	2 GB RAM
Storage	16 GB
User Interface Keyboard	Power key, Spider key, Enter, 3 standard Android keys
Audio	Built-in speaker

TOUCH SCREEN

Size	5.0" capacitive multi-touch
Resolution	1280 x 720

ENVIRONMENTAL

Temperature	
Operating	-20 °C to +50 °C (-4 °F to +122 °F)
Storage	-30 °C to +70 °C (-22 °F to +158 °F)
Humidity	.95% non-condensing (EN60068-2-30)
Water & Dust proof	IP65
Free drop	1 m (EN 60068-2-31)



Precision Laser & Instrument, Inc.
 85 11th Street | Ambridge, PA 15003
 724-266-1600 | PLI@laserinst.com

Contact your local Trimble Authorized Distribution Partner for more information

NORTH AMERICA

Trimble Inc.
 10368 Westmoor Dr
 Westminster CO 80021
 USA

EUROPE

Trimble Germany GmbH
 Am Prime Parc 11
 65479 Raunheim
 GERMANY

ASIA-PACIFIC

Trimble Navigation
 Singapore PTE Limited
 3 HarbourFront Place
 #13-02 HarbourFront Tower Two
 Singapore 099254
 SINGAPORE