



Trimble R2

GNSS RECEIVER

VERSATILITY IN THE FIELD. FLEXIBILITY FOR YOUR WORKFLOW.

Work the way you want with the Trimble® R2 GNSS receiver. Using trusted Trimble technology the R2 receiver gives you the freedom to configure a solution by simply selecting the accuracy and GNSS performance to suit your application. Capable of achieving submeter to centimeter level positioning accuracy the Trimble R2 is the answer to keep you working productively in a wide range of geospatial applications, no matter what your workflow requirements are.

Whether you are performing pole-based stakeouts, surveying on roads, in mines or on construction sites, locating buried assets such as pipes and cables, capturing GIS field assets, or carrying out precision survey measurements, the versatile Trimble R2 is purpose-built for surveyors and mapping and GIS professionals alike.

Simple to setup and easy-to-use, the Trimble R2 pairs with any Trimble handheld, Trimble Access™ controller, or consumer-grade smart device across a variety of operating systems and platforms, to deliver reliable, high quality real-time data every time.

A Simple, Rugged System for Everyday Needs

Built to withstand the rigors in the field, the rugged IP65-rated Trimble R2 receiver will work as hard as you do in tough outdoor conditions. Its one-button start up and compact, streamlined form factor makes it fast to set up and can be operated either mounted on a pole, on a backpack or on a vehicle. The field-swappable battery means all day productivity with no interruptions, keeping you focused on the job at hand.

Technology to Keep you Productive

The Trimble R2 is capable of tracking the full range of GNSS satellite constellations and augmentation systems, and comes with an integrated Trimble Maxwell™ 6 chip and 220 channels to provide you with reliable accuracy and positioning performance. Achieve higher accuracy in real-time with the flexibility to choose correction sources from traditional RTK, VRS networks, to Trimble RTX™ correction services delivered by both satellite and Internet/cellular.

Trimble has evolved its Floodlight™ satellite shadow reduction technology to ensure the R2 receiver is able to provide reliable, accurate data even in difficult GNSS environments. Equipped with this advanced GNSS technology, you can achieve remarkable improvements to position availability and accuracy when heavy overhead cover, such as tree canopy and buildings, obstruct satellite signals, making even tough GIS workflows easier.

A Complete Solution

Connect the Trimble R2 receiver to your preferred controller or mobile device via a wireless Bluetooth® connection and add proven Trimble field and office software workflows to complete the solution. Data can be collected with the customizable workflows of Trimble field software such as Trimble Access or Trimble TerraFlex™ software that allow your teams to easily collect and communicate information between the field and office in real-time. Collected data can then be processed with Trimble office software, including Trimble Business Center or TerraFlex, providing you with data rich, high-quality deliverables for your organization.

For a simple, configurable, field-to-office solution, the innovative and flexible Trimble R2 GNSS receiver enables you to work accurately and productively your way.

Key Features

- ▶ A professional solution for geospatial applications ranging from sub-meter to centimeter accuracies to support any GIS or survey-grade workflow
- ▶ Easily collect data by pairing with devices such as smartphones, tablets or Trimble handhelds using Trimble Survey and GIS software
- ▶ Fast to setup, easy to use, keeping you productive and focused at your task at hand
- ▶ Supports multiple satellite constellations and correction sources for accurate data at any location
- ▶ Trimble Maxwell 6 chip with 220 channels and leading GNSS technology maximizes data quality



Trimble R2 GNSS RECEIVER

CONFIGURATION OPTION

Type	Smart antenna
Base operation	Yes, Logging only
Rover operation	Yes
Rover position update rate	1 Hz, 2 Hz, 5 Hz
Rover operation within a VRS Now™ network	Yes

MEASUREMENTS

- Advanced Trimble Maxwell 6 custom GNSS chip
- High-precision multiple correlator for L1/L2 pseudo-range measurements
- Unfiltered, unsmoothed pseudo-range measurements data for low noise, low multipath error, low-time domain correlation, and high-dynamic response
- Very low noise carrier phase measurements with <1 mm precision in a 1 Hz bandwidth
- Signal-to-noise ratios reported in dB-Hz
- Trimble EVEREST™ multipath signal rejection
- Proven Trimble low elevation tracking technology
- 220-channel GNSS
- 4-channel SBAS (WAAS/EGNOS/MSAS/GAGAN)

POSITIONING PERFORMANCE

SBAS (WAAS/EGNOS/MSAS/GAGAN) Positioning¹

Horizontal accuracy	±0.50 m (1.6 ft)
Vertical accuracy	±0.85 m (2.8 ft)

Code Differential GPS Positioning²

Correction type	DGPS RTCM 2.x
Correction source	IBSS
Horizontal accuracy	±(0.25 m + 1 ppm) RMS ±(0.8 ft + 1 ppm)
Vertical accuracy	±(0.50 m + 1 ppm) RMS ±(1.6 ft + 1 ppm)

Static GNSS Positioning

Static and Fast Static

Horizontal	3 mm + 0.5 ppm RMS
Vertical	5 mm + 0.5 ppm RMS

Trimble RTX Positioning^{3,4}

CenterPoint® RTX	Horizontal accuracy: 4 cm RMS	Vertical accuracy: 9 cm RMS
FieldPoint RTX™	10 cm Horizontal RMS	
RangePoint™ RTX	30 cm Horizontal RMS	
ViewPoint RTX™	50 cm Horizontal RMS	

RTK Positioning²

Horizontal accuracy	10 mm + 1 ppm RMS (0.033 ft + 1 ppm RMS)
Vertical accuracy	20 mm + 1 ppm RMS (0.065 ft + 1 ppm RMS)

Network RTK²

Horizontal accuracy	10 mm + 0.5 ppm RMS (0.033 ft + 0.5 ppm RMS)
Vertical accuracy	20 mm + 0.5 ppm RMS (0.065 ft + 0.5 ppm RMS)

BATTERY AND POWER

Internal	Replaceable internal battery 7.4 V, 2800 mA-hr, Lithium-ion
External	Power input on the Mini-B USB connector, non-charging as per the USB standard 10 W USB adapter
Power consumption	4.95 W (VFD 100%), 3.7 W (VFD 12.5%) at 18 V, in rover mode

Operation time on internal battery

Rover	5 hours; varies with temperature
-------	----------------------------------

MECHANICAL

User interface	LED indicators for receiver status On/Off key for one-button startup
Dimensions	14.0 cm (5.5 in) diameter x 11.4 cm (4.5 in) height
Weight	1.08 kg (2.38 lb) receiver only

ENVIRONMENTAL

Temperature	Operating: -20 °C to +55 °C (-4 °F to +131 °F) Storage: -40 °C to +75 °C (-40 °F to +167 °F)
Humidity	100% condensing
Waterproof	IP65
Pole drop	Designed to survive a 2 m (6.6 ft) drop onto all faces and corners onto concrete (25C)
Shock	Non-operating: To 75 g, 6 ms, saw-tooth Operating: To 40 g, 10 ms, saw-tooth 100 shock events at 2 Hz rate
Vibration	MIL-STD-810G (Operating), Method 514.6, Procedure I, Category 4, Figure 514.6C-1 (Common Carrier, US Highway Truck Vibration Exposure) Total Grms levels applied are 1.95 g

INTERNAL ANTENNA

Frequency Range	L1/L2 (GPS, GLONASS, Galileo, BeiDou, QZSS), MSS (RTX), L1 SBAS
-----------------	---

COMMUNICATIONS

USB	1 USB 2.0 (Type B) device
Wi-Fi	Simultaneous client and access point (AP) modes
Bluetooth wireless technology	Fully-integrated, fully-sealed 2.4 GHz Bluetooth module ⁵
Network protocols	HTTP (web browser GUI); NTP Server, TCP/IP or UDP; NTRIP v1 and v2, Client mode; mDNS/uPnP service discovery; dynamic DNS; eMail alerts; network link to Google Earth; PPP and PPPoE
Supported data formats	Correction inputs: CMR, CMR+™, CMRx, RTCM 2.x, RTCM 3 Correction outputs: None Data outputs: NMEA, GSOF
External GSM/GPRS modem, cell phone support	
Integrated receiving radio (optional)	Integrated 450 MHz UHF Radio
Channel spacing (450 MHz)	12.5 and 25 kHz
Sensitivity (450 MHz)	-103 dBm, GMSK 9600 baud 25kHz channel spacing
Data Storage	48 MHB internal memory ⁶

COMPLIANCE


FCC Part 15 Subpart B (Class B Device) and Subpart C; CAN ICES-3(B)/NMB-3(B), RSS-Gen and RSS-210; R&TTE Directive: EN 301 489-1/-3/-5/-17, EN 300 440, EN 300 328, EN 300 330, EN 60950, EN 50371; ACMA Regulatory Compliance Mark (RCM); CE mark compliance: UN ST/SG/AC.10.11/Rev. 3, Amend. 1 (Lithium-ion Battery, charger not included), UN ST/SG/AC.10/27/Add. 2 (Lithium-ion Battery, charger not included); C-Tick; WEEE and RoHS compliant.

"Made for iPhone" and "Made for iPad" mean that an electronic accessory has been designed to connect specifically to iPhone or iPad respectively, and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards. Please note that the use of this accessory with iPhone or iPad may affect wireless performance.

iPad, iPhone and Retina are trademarks of Apple Inc., registered in the U.S. and other countries. iPad mini is a trademark of Apple Inc.

- Depends on SBAS system performance.
- Accuracy and reliability may be subject to anomalies such as multipath, obstructions, satellite geometry, interference and atmospheric conditions. Always follow recommended practices.
- CenterPoint RTX accuracy is typically achieved within 5 minutes in select regions, and within 30 minutes worldwide. FieldPoint RTX accuracy is typically achieved within 5 minutes in select regions, and within 15 minutes worldwide. RangePoint RTX and ViewPoint RTX accuracy is typically achieved within 5 minutes worldwide.
- Receiver accuracy and convergence time varies based on GNSS constellation health, level of multipath, and proximity to obstructions such as large trees and buildings.
- Bluetooth type approvals are country-specific. For more information, contact your local Trimble office or representative.
- The actual available capacity of the internal memory is less than the specified capacity because the firmware occupies part of the memory. The available capacity may change when you upgrade receiver firmware.

Specifications subject to change without notice.



Precision Laser & Instrument, Inc.
85 11th Street | Ambridge, PA 15003
724-266-1600 | PLI@laserinst.com

Contact your local Trimble Authorized Distribution Partner for more information

NORTH AMERICA

Trimble Navigation Limited
10368 Westmoor Dr
Westminster CO 80021
USA

EUROPE

Trimble Germany GmbH
Am Prime Parc 11
65479 Raunheim
GERMANY

ASIA-PACIFIC

Trimble Navigation
Singapore Pty Limited
80 Marine Parade Road
#22-06, Parkway Parade
Singapore 449269
SINGAPORE

