



# Trimble RTS673

## ROBOTIC TOTAL STATION

### ACCURACY FOR EVERYDAY APPLICATIONS

With the Trimble® RTS673 Robotic Total Station contractors can improve efficiency and accuracy for common layout tasks in building construction.

#### For Everyday Layout

Automate building layout tasks with total confidence. The Trimble RTS673 streamlines layout of sleeves, hangers, stub-up, anchor bolts, concrete forms, utilities, or cable trays. Versatile enough for light topographic projects and as-built data collection, the RTS673 can handle almost any challenge on the job site.

### UNSURPASSED TOTAL STATION TECHNOLOGY

Trimble MagDrive™ Servo Technology provides for exceptional speed and accuracy with smooth, silent operation.

Trimble SurePoint™ Technology ensures accurate measurements by automatically correcting for unwanted movement due to wind, sinkage, and other factors.

Trimble MultiTrack™ technology locks on and tracks passive prisms for control measurements and active targets for dynamic measurement, stakeout and grade control.

### BUILT FOR CONSTRUCTION

- ▶ For construction applications, you need a measurement solution with optimal speed, accuracy and reliability. With the Trimble DR HP Precision EDM you have the flexibility to tackle the most demanding projects.
- ▶ Visually mark points, with high precision, using the Class 2 Laser Pointer.
- ▶ Automatic Servo Focus sets the optical focus for quick manual aiming when laying out points in DR mode.
- ▶ Combine with Trimble Field Link software running on the Trimble Field Tablet to optimize your accuracy and productivity.

### Key Features

- ▶ MagDrive technology for maximum speed and efficiency
- ▶ MultiTrack technology offers the choice between passive and active tracking
- ▶ Quickly mark layout points with Class 2 laser Pointer
- ▶ Lock onto your target faster in robotic mode with Track-Light technology



# Trimble RTS673 ROBOTIC TOTAL STATION

## PERFORMANCE

Angle measurement accuracy (standard deviation based on DIN 18723) ..... 3" (0.9 mgon)  
 Angle display (least count) ..... 0.1" (0.01 mgon)  
 Distance measurement

Typical Accuracy	50 m (164 ft)	100 m (328 ft)	200 m (656 ft)	300 m (984 ft)
Prism mode Standard Tracking	2 mm (5/64") 5 mm (13/64")	3 mm (1/8") 5 mm (13/64")	4 mm (5/32") 6 mm (15/64")	6 mm (15/64") 8 mm (5/16")
DR mode Standard Tracking	3 mm (1/8") 10 mm (25/64")	4 mm (5/32") 10 mm (25/64")	5 mm (13/64") 11 mm (7/16")	6 mm (5/64") 12 mm (15/32")

Measuring time  
 Prism mode  
 Standard ..... 2.5 s  
 Tracking ..... 0.4 s  
 Averaged observations ..... 2.5 s per measurement  
 DR mode  
 Standard ..... 3–15 s  
 Tracking ..... 0.4 s

Range (under standard clear conditions<sup>1,2</sup>)  
 Prism mode  
 1 prism ..... 3,000 m (9,800 ft)  
 Shortest range ..... 1.5 m (4.9 ft)  
 DR mode

	Good (Good visibility, low ambient light)	Normal (Normal visibility, moderate sunlight, some heat shimmer)	Difficult (Haze, object in direct sunlight, turbulence)
White card (90% reflective) <sup>3</sup>	> 150 m (492 ft)	150 m (492 ft)	70 m (229 ft)
Gray card (18% reflective) <sup>3</sup>	> 120 m (394 ft)	120 m (394 ft)	50 m (164 ft)

Shortest range ..... 1.5 m (4.9 ft)

## EDM SPECIFICATIONS

Light source ..... Laserdiode 660 nm; Laser class 1 in Prism mode  
 Laser class 2 in DR mode  
 Laser pointer coaxial (standard) ..... Laser class 2  
 Beam divergence Prism mode  
 Horizontal ..... 4 cm/100 m (0.13 ft/328 ft)  
 Vertical ..... 4 cm/100 m (0.13 ft/328 ft)  
 Beam divergence DR mode  
 Horizontal ..... 2 cm/50 m (0.066 ft/164 ft)  
 Vertical ..... 2 cm/50 m (0.066 ft/164 ft)  
 Atmospheric correction ..... -130 ppm to 160 ppm continuously

## GENERAL SPECIFICATIONS

Leveling  
 Circular level in tribrach ..... .8/2 mm (8'/0.007 ft)  
 Automatic level compensator  
 Type ..... Centered dual-axis  
 Accuracy ..... 0.5" (0.15 mgon)  
 Range ..... ±5.4" (±100 mgon)  
 Servo system ..... MagDrive servo technology, integrated servo/angle sensor; electromagnetic direct drive  
 Rotation speed ..... 115 degrees/s (128 gon/s)  
 Rotation time Face 1 to Face 2 ..... 2.6 s  
 Positioning speed 180 degrees (200 gon) ..... 2.6 s  
 Clamps and slow motions ..... Servo-driven, endless fine adjustment  
 Centering  
 Centering system ..... Trimble 3-pin  
 Optical plummet ..... Built-in optical plummet  
 Magnification/shortest focusing distance ..... 2.3x/0.5 m to infinity (1.6 ft to infinity)  
 Telescope  
 Magnification ..... 30x  
 Aperture ..... 40 mm (1.57 in)  
 Field of view at 100 m (328 ft) ..... 2.6 m at 100 m (8.5 ft at 328 ft)  
 Shortest focusing distance ..... 1.5 m (4.9 ft) to infinity  
 Illuminated crosshair ..... Variable (10 steps)  
 Autofocus ..... Standard  
 Tracklight built in ..... Not available in all models  
 Operating temperature ..... -20° C to +50° C (-4° F to +122° F)  
 Dust and water proofing ..... IP55  
 Humidity ..... 100% condensing  
 Power supply  
 Internal battery ..... Rechargeable Li-Ion battery 10.8V, 6.5Ah, 70Wh  
 Operating time<sup>4</sup>  
 One internal battery ..... Approx. 6.5 hours  
 Three internal batteries in multi-battery adapter ..... Approx. 18 hours  
 Robotic holder with one internal battery ..... 13.5 hours  
 Operating time with video robotic<sup>4</sup>  
 One battery ..... 5.5 hours  
 Three batteries in multi-battery adapter ..... 17 hours  
 Weight  
 Instrument (Servo/Autolock\*) ..... 5.15 kg (11.35 lb)  
 Instrument (Robotic) ..... 5.25 kg (11.57 lb)  
 Trimble CU controller ..... 0.4 kg (0.88 lb)  
 Tribrach ..... 0.7 kg (1.54 lb)  
 Internal battery ..... 0.35 kg (0.77 lb)  
 Trunnion axis height ..... 196 mm (7.71 in)  
 Communication ..... USB, Serial, Bluetooth<sup>5</sup>  
 Security ..... Dual-layer password protection

## ROBOTIC RANGE

Autolock and Robotic range<sup>2</sup>  
 Passive prisms ..... 500–700 m (1,640–2,297 ft)  
 Trimble MultiTrack Target ..... 800 m (2,625 ft)  
 Autolock pointing precision at 200 m (656 ft) (standard deviation)<sup>2</sup>  
 Passive prisms ..... <2 mm (0.007 ft)  
 Trimble MultiTrack Target ..... <2 mm (0.007 ft)  
 Shortest search distance ..... 0.2 m (.65 ft)  
 Search time (typical)<sup>6</sup> ..... 2–10 s

- Standard clear: No haze. Overcast or moderate sunlight with very light heat shimmer.
- Range and accuracy depend on atmospheric conditions, size of prisms and background radiation.
- Kodak Gray Card, Catalog number E1527795.
- The capacity in -20 °C (-5 °F) is 75% of the capacity at +20 °C (68 °F).
- Bluetooth type approvals are country specific. Contact your local Trimble Authorized Distribution Partner for more information.
- Dependent on selected size of search window.



Specifications subject to change without notice.



Precision Laser & Instrument, Inc.  
 85 11th Street  
 Ambridge, PA 15003  
 (724) 266-1600

Contact your local Trimble Authorized Distribution Partner for more information

TRIMBLE MEP  
 116 Inverness Drive East, Suite 210  
 Englewood, CO 80112  
 Phone: 1-800-234-3758

